

# cisco ccna lab answers

Published: September 27, 2026 | Index ID: #-

---

## Introduction

---

Preparing for the Cisco Certified Network Associate (CCNA) exam requires more than memorizing theory; it demands hands-on experience with real network devices or simulators. While textbooks and video tutorials lay the groundwork, nothing replaces the confidence gained from troubleshooting a live lab. Many candidates turn to the internet for **cisco ccna lab answers**, hoping to shortcut the learning curve. However, blindly copying answers can hinder deeper understanding. In this article we explore why lab answers are valuable, how to use them responsibly, and provide detailed solutions for some of the most common CCNA lab exercises. By the end you'll have a practical guide that balances study efficiency with genuine skill development.

## Why Lab Answers Matter in CCNA Preparation

---

CCNA labs test your ability to apply concepts under realistic conditions. They simulate the challenges you'll face in the workplace: configuring routers, setting up VLANs, managing routing protocols, and diagnosing connectivity issues. When you encounter a lab, the process typically follows these steps:

- Read the lab instructions carefully.
- Identify the required configuration tasks.
- Execute commands on the devices.
- Verify functionality with ping, traceroute, and show commands.
- Document results and troubleshoot failures.

Lab answers provide a reference point for each of these stages. They help you verify that your approach is correct, identify gaps in your knowledge, and learn the most efficient command sequences. Nonetheless, they should be used as a learning aid rather than a shortcut.

## Common Reasons Candidates Seek Lab Answers

1. **Time Constraints:** Exam deadlines can be tight, and students may feel pressured to finish labs quickly.
2. **Complexity of Commands:** Cisco IOS syntax can be intimidating, especially when dealing with advanced features like OSPF authentication or ACL extensions.
3. **Troubleshooting Stumbling Blocks:** When a lab fails, it's easy to become frustrated and search online for the exact command that solves the problem.
4. **Verification of Work:** Confirming that your configuration matches the expected outcome ensures you're on the right track.

## Common CCNA Lab Topics Covered by Answers

---

Below is a concise list of the most frequently encountered labs in CCNA training programs. For each topic, we'll provide a typical lab scenario, followed by a detailed set of answers.

- Basic Router and Switch Configuration
- VLANs, Trunking, and Inter-VLAN Routing

- Static Routing and Default Routes
- Dynamic Routing Protocols: OSPF and EIGRP
- Network Address Translation (NAT) and Access Control Lists (ACLs)
- Troubleshooting Connectivity Issues
- Security Features: Port Security and DHCP Snooping

## Lab 1: Configuring Basic Router Settings

---

Many CCNA labs begin with the fundamental task of configuring a router's basic settings. This includes hostname, interface IP addresses, and enabling the device.

### Lab Scenario

Configure Router R1 with the following parameters:

- Hostname: R1
- Interface FastEthernet0/0: IP 192.168.1.1/24
- Interface FastEthernet0/1: IP 10.0.0.1/30
- Enable SSH access with username admin and password cisco123.

### Lab 1 Answers

1. Set Hostname

```
R1> enable
```

```
R1# configure terminal
```

```
R1(config)# hostname R1
```

2. Configure Interfaces

```
R1(config)# interface FastEthernet0/0
```

```
R1(config-if)# ip address 192.168.1.1 255.255.255.0
```

```
R1(config-if)# no shutdown
```

```
R1(config-if)# exit
```

```
R1(config)# interface FastEthernet0/1
```

```
R1(config-if)# ip address 10.0.0.1 255.255.255.252
```

```
R1(config-if)# no shutdown
```

```
R1(config-if)# exit
```

3. Enable SSH

```
R1(config)# ip domain-name example.com
```

```
R1(config)# crypto key generate rsa
```

```
Key modulus size? 512 (recommended 2048)
```

```
...
```

```
R1(config)# username admin privilege 15 secret cisco123
```

```
R1(config)# line vty 0 4
```

```
R1(config-line)# login local
```

```
R1(config-line)# transport input ssh
```

```
R1(config-line)# exit
```

4. Save Configuration

```
R1# write memory
```

## Lab 2: VLANs and Trunking

---

Virtual LANs (VLANs) allow network segmentation, improving performance and security. This lab focuses on creating VLANs, assigning switch ports, and configuring trunk links.

### Lab Scenario

On Switch SW1:

- Create VLAN 10 (Sales) and VLAN 20 (Engineering).
- Assign FastEthernet0/1 to VLAN 10 and FastEthernet0/2 to VLAN 20.
- Configure FastEthernet0/24 as a trunk port carrying both VLANs.

### Lab 2 Answers

1. Create VLANs

```
SW1> enable
```

```
SW1# configure terminal
```

```
SW1(config)# vlan 10
```

```
SW1(config-vlan)# name Sales
```

```
SW1(config-vlan)# exit
```

```
SW1(config)# vlan 20
```

```
SW1(config-vlan)# name Engineering
```

```
SW1(config-vlan)# exit
```

2. Assign Ports to VLANs

```
SW1(config)# interface FastEthernet0/1
```

```
SW1(config-if)# switchport mode access
```

```
SW1(config-if)# switchport access vlan 10
```

```
SW1(config-if)# exit
```

```
SW1(config)# interface FastEthernet0/2
```

```
SW1(config-if)# switchport mode access
```

```
SW1(config-if)# switchport access vlan 20
```

```
SW1(config-if)# exit
```

3. Configure Trunk Port

```
SW1(config)# interface FastEthernet0/24
```

```
SW1(config-if)# switchport mode trunk
```

```
SW1(config-if)# switchport trunk allowed vlan 10,20
```

```
SW1(config-if)# exit
```

4. Verify Configuration

```
SW1# show vlan brief
```

```
SW1# show interfaces trunk
```

## Lab 3: Routing Protocols – Static, OSPF, and EIGRP

---

Routing protocols determine how packets travel across networks. This lab covers the configuration of static routes, OSPF, and EIGRP on multiple routers.

### Lab Scenario

Set up the following network:

- Router R1 connects to R2 via FastEthernet0/1.
- Router R2 connects to R3 via FastEthernet0/2.

- Configure static routes on each router to reach the remote subnet.
- Implement OSPF area 0 on all routers and verify adjacency.
- Configure EIGRP with AS 100 on R1 and R3 only.

### Lab 3 Answers

#### 1. Static Routing

```
R1(config)# ip route 10.0.2.0 255.255.255.0 10.0.0.2
```

```
R2(config)# ip route 10.0.1.0 255.255.255.0 10.0.0.1
```

```
R2(config)# ip route 10.0.3.0 255.255.255.0 10.0.0.3
```

```
R3(config)# ip route 10.0.1.0 255.255.255.0 10.0.0.2
```

#### 2. OSPF Configuration

```
R1(config)# router ospf 1
```

```
R1(config-router)# network 10.0.0.0 0.0.0.255 area 0
```

```
R1(config-router)# exit
```

```
R2(config)# router ospf 1
```

```
R2(config-router)# network 10.0.0.0 0.0.0.255 area 0
```

```
R2(config-router)# exit
```

```
R3(config)# router ospf 1
```

```
R3(config-router)# network 10.0.0.0 0.0.0.255 area 0
```

```
R3(config-router)# exit
```

#### 3. EIGRP Configuration (R1 & R3)

```
R1(config)# router eigrp 100
```

```
R1(config-router)# network 10.0.0.0 0.0.0.255
```

```
R1(config-router)# exit
```

```
R3(config)# router eigrp 100
```

```
R3(config-router)# network 10.0.0.0 0.0.0.255
```

```
R3(config-router)# exit
```

#### 4. Verification

```
R1# show ip ospf neighbor
```

```
R2# show ip ospf neighbor
```

```
R3# show ip ospf neighbor
```

```
R1# show ip eigrp neighbors
```

```
R3# show ip eigrp neighbors
```

## Lab 4: NAT and ACLs

Network Address Translation (NAT) allows multiple devices to share a single public IP address, while Access Control Lists (ACLs) control traffic flow. This lab demonstrates PAT (Port Address Translation) and a standard ACL to permit internal traffic.

### Lab Scenario

On Router R1:

- Configure NAT to translate internal 192.168.1.0/24 to the public IP 203.0.113.5.
- Apply a standard ACL that permits only 192.168.1.0/24 to access the internet.

## Lab 4 Answers

### 1. Define ACL

```
R1(config)# access-list 10 permit 192.168.1.0 0.0.0.255
```

### 2. Configure NAT Pool

```
R1(config)# ip nat pool PUBLIC 203.0.113.5 203.0.113.5 netmask 255.255.255.255
```

```
R1(config)# ip nat inside source list 10 pool PUBLIC overload
```

### 3. Set Inside/Outside Interfaces

```
R1(config)# interface FastEthernet0/0
```

```
R1(config-if)# ip nat inside
```

```
R1(config-if)# exit
```

```
R1(config)# interface FastEthernet0/1
```

```
R1(config-if)# ip nat outside
```

```
R1(config-if)# exit
```

### 4. Verification

```
R1# show ip nat translations
```

```
R1# show access-lists 10
```

## Lab 5: Troubleshooting Connectivity Issues

---

Troubleshooting is a core skill for any network engineer. In this lab, you'll identify and resolve common connectivity problems.

### Lab Scenario

Router R1 and R2 are connected, but a device on R1's LAN cannot ping R2. The device shows a default gateway of

## Baca Juga (Artikel Terkait)

---

- [chicago public schools payroll schedule](http://www.bbgglobalsolutions.com/chicago-public-schools-payroll-schedule.pdf)

URL: <http://www.bbgglobalsolutions.com/chicago-public-schools-payroll-schedule.pdf>

- [chicago manual style cms format](http://www.bbgglobalsolutions.com/chicago-manual-style-cms-format.pdf)

URL: <http://www.bbgglobalsolutions.com/chicago-manual-style-cms-format.pdf>

- [chicago manual of style 14th edition full download](http://www.bbgglobalsolutions.com/chicago-manual-of-style-14th-edition-full-download.pdf)

URL: <http://www.bbgglobalsolutions.com/chicago-manual-of-style-14th-edition-full-download.pdf>

- [chicago growth of a metropolis](http://www.bbgglobalsolutions.com/chicago-growth-of-a-metropolis.pdf)

URL: <http://www.bbgglobalsolutions.com/chicago-growth-of-a-metropolis.pdf>

Tags: #cisco #ccna #answers









